

## AUTHOR INDEX TO VOLUME 14

- Aceves, S. M., 143  
Ahmadi, G., 289
- Bae, C., 159  
Balachandran, W., 175  
Bar-Kohany, T., 495  
Becker, J., 15  
Blaisdell, G. A., 37
- Chaves, H., 589  
Chehroudi, B., 81  
Chigier, N., 459  
Choi, J., 159  
Clack, H. L., 265
- Downey, D., 93, 111
- Gemci, T., 459  
Giles, D. K., 93, 111  
Gorman, S., 525
- Hassa, C., 15  
Heister, S. D., 37  
Heitz, D., 15  
Hiroyasu, H., 477  
Ho, T. C., 459
- Inamura, T., 375
- Kholmer, V., 341  
Kim, M. C., 175  
Kimoto, K., 1  
Kirmse, C., 589  
Koshland, C. P., 265  
Kvasnak, W., 289
- Langrish, T. A. G., 355  
Lee, C. H., 545  
Lee, C. S., 545  
Lee, K. H., 545  
Lee, S., 159  
Lee, S. Y., 175  
Li, T., 477  
Lucas, D., 265
- Martinez-Frias, J., 143  
Mehring, C., 397
- Namba, K., 1  
Nishida, K., 477
- Obermeier, F., 589
- Rashkovan, A., 341  
Reitz, R. D., 53
- Sadik, S., 563  
Sahai, V., 143  
Sawyer, R. F., 265  
Schmidt, D. J., 289  
Sher, E., 341, 495  
Shrimpton, J. S., 127  
Sirignano, W. A., 397  
Slaughter, D. C., 93, 111  
Song, Y., 437  
Sözbir, N., 191  
Spanoghe, P., 511  
Stepowski, D., 243  
Steurbaut, W., 511
- Talley, D., 81  
Tanner, F. X., 211  
Tomoda, T., 375
- Valencia-Bejarano, M., 355  
Van der Meeran, P., 511  
Van Eckout, H., 511
- Werquin, O., 243  
Widmann, J. F., 525
- Xu, C., 37
- Yakut, K., 459  
Yao, S.-C., 191  
Yi, Y., 53  
Yule, A. J., 127
- Zhang, M., 437  
Zimmels, Y., 563



## SUBJECT INDEX TO VOLUME 14

### A

Acetone, 459  
 Adjuvants, 511  
 Agricultural spraying, 93  
 Air cooling, 191  
 Air density, 15  
 Air jet  
     impingement, 191  
     velocities, 191  
 Air-blast atomizer, 265  
 Airflow rate, 355  
 Air-fuel mixing process, 477  
 Annular volume, 477  
 Asphalt/water (As/W), 1  
 Atomization, 1, 127, 211  
     mechanism, 545  
     model, 437  
     of gasoline fuel, 341  
     of pesticides, 511  
     of water, 459  
     performance, 175  
     process, 437  
     quality, 127  
 Atomized  
     fuel droplets, 289  
     spray, 545  
 Atomizer  
     electrical characteristics, 127  
     internal geometry, 127  
 Atomizing gas streams, 265  
 Axisymmetric  
     disturbances, 397  
     ligaments, 563  
 Axipolar instability parameter, 563

### B

Bicomponent liquid flashing, 495  
 Biological targets, 93  
 Boundary conditions, 53  
 Breakup  
     characteristics, 53  
     criterion, 211  
     of high-speed jets, 53  
     pattern, 459  
 Bubble  
     growth in an expansion chamber, response, 37, 495

### C

C heavy oil, 1  
 Capillary  
     stability, 397  
     tube voltage, 175  
 Cascade atomization, 211  
 Cavitating flow, 37  
 Charge injection  
     atomizers, 127  
     electrostatic atomizer design, 127  
     site, 127  
 Charged sprays, 127  
 CO<sub>2</sub> content on the spray characteristics, 341  
 Coaxial air-blast injector, 243  
 Cold-flow experiments, 265  
 Combustion  
     efficiency, 265  
     experiments, 1  
 Continuously variable atomization, 265  
 Counterswirling, 15  
 Cross-flow velocity, 37, 159  
 Cryogenic nitrogen jets, 81  
 Cylindrical fluid film, 265

### D

D.I. gasoline  
     engine, 477  
     injector, 477  
 Deformation velocities, 211  
 Deforming  
     droplets, 289  
     ellipsoidal droplets, 289  
 Deposition target, 93  
 Dilatational or sinuous three-dimensional  
     modulations, 397  
 Dilatational waves, 397  
 Direct injection, 159  
     gasoline engine, 477  
     spark-ignition (DISI) engine, 375  
 Discharge coefficient, 37  
 Discrete  
     blobs, 53  
     targets, 93  
 Dispersed flames, 1  
 Dispersion equation, 563  
 Distilling crude oils, 1  
 Double-annular air flow, 15

- D**
- Drop
    - breakup model, 211
    - disintegration mechanism, 211
    - generation, 175
    - size, 53
    - size distribution, 175
  - Droplet
    - breakup mechanisms, 545
    - coalescence, 355
    - diameter, 143, 375
    - dispersions, 265
    - distribution peaks, 375
    - distribution, 437, 477
    - evolution with distance, 355
    - mean sizes, 355
    - size, 477
    - size distributions, 525
    - spreading, 143
    - turbulent diffusivities, 289
    - velocity, 289
  - Droplets, 15
- E**
- Effects of different operating conditions, 355
  - Effervescent atomization, 341
  - Electrical conductivity, 175
  - Electrohydrodynamic atomization process, 175
  - Emission, 1
  - Emission characteristics, 1
  - Engine
    - cylinders, 159
    - performance, 545
  - Euclidean distance mapping (EDM), 81
  - Eulerian approach, 53
  - Evaporating droplets, 289
  - Expansion chamber, 341, 495
- F**
- Filament shedding, 397
  - Film
    - rupture, 397
    - topology, 397
  - Fine liquid (water) drops, 175
  - Flash atomization of water and water/acetone solutions, 459
  - Flight of spray droplet packets, 111
  - Flight time, 111
  - Fluctuating fluid velocity, 289
- G**
- Gas
    - characteristics of residual oils, 1
    - turbine, 15
  - Gasoline direct injection, 159, 545
  - Geometric proportions, 341
  - Glass tempering, 191
  - Global spray structure, 545
- H**
- Heat transfer
    - coefficient, 191
    - distribution, 191
  - Herbicide efficacy, 93
  - Herbicide spraying, 111
  - High spatial resolution, 93
  - High-pressure
    - air, 191
    - swirl injector, 477, 545
    - driven liquid fuel sprays, 211
  - High-speed
    - annular air flow, 243
    - jet experiments, 53
  - High-velocity dense sprays, 211
  - Hologram, 477
  - Holographic results, 477
  - Holography, 47
  - Homogeneous flow model, 37
  - Hydrocarbon
    - emissions, 159
    - liquids, 459

**I**

- Impingement of a liquid jet, 375
- Independent control of droplet size, 265
- Injection
  - pressure, 341
  - temperature, 459
  - velocity, 53
- Inner-nozzle disturbances, 211
- Instability at lower polar wave numbers, 563
- Insulating liquids, 127
- Interdroplet spacing, 265
- Interior gas-liquid flows, 437
- Intermittent spraying, 111
- Isopropyl alcohol sprays, 265

**J**

- Jet
  - breakup length, 53
  - diameter, 53
  - liquid, 53, 289
  - velocity, 111
- Jets,
  - low-speed water, 243
  - pulsed, 93
  - subcritical, 81
  - supercritical, 81
  - water mist, 191

**K**

- Kerosene fuel spray, 15
- KromekoteTM cards, 93

**L**

- Laser
  - diagnostics, 265
  - diffraction measurements, 355
  - method, 477
  - Doppler anemometry (LDA), 15
  - particle size analyzer, 341
- Leading spray, 477
- Light-scattering technique, 355
- Limiting polar wave number, 563
- Linear jet stability, 53
- Liquid
  - deposition, 93
  - ellipsoidal droplets, 289

- film generated, 375
- flow rate, 175
- jet, 53, 289, 563
- property, 111
- sheet primary breakup, 437
- volume fraction , 243
- Local probability density function (PDF), 243
- Low-speed water jet, 243

**M**

- Madejski splat-quench solidification model, 143
- Madejski's model, 143
- Malvern X-Mastersizer, 341
- Manifold, 37
- Mean droplet size, 265, 375
- Mean spray density, 265
- Mean-square fluctuation velocities, 289
- Metal-coated silica tube, 175
- Microdrift, 93
- Microexplosion effect, 1
- Microspraying , 93
- Mist cooling, 191
- Modulated swirling liquid sheets, 397
- Monte Carlo simulations, 525
- Multidimensional kiva computational fluid dynamics (CFD), 53
- Multilayer drop-stripping model, 53
- Multimodal instability, 563
- Multinozzle atomization on coalescence, 355

**N**

- Needle electrode, 127
- Nitrogen, 459
- Noncavitating flow, 37
- No<sub>x</sub>, 1
- Nozzle
  - effects, 111
  - flow model, 53
  - internal flow, 53
  - materials , 175
  - type, 511
- Nuclei formation, 495
- Nukiyama-Tanasawa distribution function, 545

**O**

- Optimization of combustion systems, 545
- Orifices, 37

**P**

- Parametric study, 243  
 Particle image velocimetry (PIV), 525  
 Penetration distance, 477  
 Phase doppler anemometer (PDA) system, 159  
 Phase Doppler  
     anemometry (PDA), 15, 545  
     particle analyzer (PDPA), 375  
 Physicochemical processes, 265  
 Pitch, 1  
 PIV measurements, 525  
 Plain-jet-in-crossflow injection, 15  
 Point-plane geometry, 127  
 Polar  
     instability, 563  
     surface disturbances, 563  
 Pollutant  
     emissions, 159  
     formation, 265  
 Polyacrylamide polymer, 93  
 Polydisperse sprays, 525  
 Polydispersity, 525  
 Polyethylene oxide polymer, 93  
 Prefilming double-annular air-blast atomizer (PFDAAA), 265  
 Pressure, 459  
 Pressure drop  
     at discharge orifice, 495  
     at the inlet orifice, 495  
 Pressure effects, 81  
 Preswirl spray, 477  
 Propellant  
     gas, 459  
     liquid, 459  
 Pulsed  
     jet spray, 111  
     jets, 93  
 Pulsed microspray jets, 93  
 Pulsed-jet microspray applications, 93

**Q**

- Quantitative characteristics of sprays, 545

**R**

- Rayleigh-Plesset equation, 37  
 Reducing fuel consumption, 159  
 Residual oils, 1

- Residual water mixture, 1  
 Rosin-Rammler distribution function, 545

**S**

- Sauter mean diameter (SMD), 265, 341, 375  
 Separate-phase model, 437  
 Simulated turbulent flow field, 289  
 Single-component fuel, 341  
 Sinuous oblique waves, 397  
 Size-classified spray structure, 545  
 Solutions for axipolar instability parameters of hollow jets, 563  
 Spatial distribution, 477  
 Special-design injector, 495  
 Spindle mode, 175  
 Spiraling filaments, 397  
 Spray  
     and flow-field interaction, 159  
     angle, 341  
     atomization, 53  
     combustion research, 265  
     current measurements, 127  
     density measures, 265  
     dispersion, 15  
     formation from jets, 563  
     liquid penetration length, 53  
     performance, 511  
     polydisperse, 525  
     prediction, 53  
     quality, 459  
     structures, 477  
 Standard atomization models, 53  
 Steady-state atomization process, 341  
 Subcritical jets, 81  
 Superimposed disturbances in spray formation, 563  
 Superimposed sequence of nonaxial and polar disturbances, 563  
 Subsonic effervescent atomization, 495  
 Supercritical jets, 81  
 Superheat degree, 495  
 Surface  
     structure of a blob, 53  
     tension, 111  
     wettability of tubes, 175  
 Surfactants used for cropping, 511  
 Swirl  
     grooves, 477  
     velocity, 477  
 Swirling conical films, 397

## T

- Tangential grooves, 477
- Taylor drop oscillator, 211
- Toroidal forms of drops, 563
- Tube voltage, 175
- Turbulent spray, 289
- Twin-fluid
  - atomizer, 1
  - fluid design, 265

## V

- Vaporization model, 289
- Variable spray, 265
- Velocity gradient components, 289
- Vortex structure, 37

## W

- Wall impingement injector, 375
- Water
  - flow rate, 355
  - mist, 191
  - mist cooling, 191
  - mist jet, 191
  - mixtures, 1
- Wave growth, 53
- Wave numbers
  - axial, 563
  - polar, 563

## Y

- Y-jet nozzle, 437

